

Co; Ltd
ER-0002

Pall Filter (BeiJing) Co., Ltd
Tel: 021-62371988 Fax: 021-62372088

Dragon Aromatics (Zhangzhou)
询价号: 413061-1000-EN30-T

~~0.4 1. 11 F 204A/B, 13 F 204A/B, Feed Filters~~

Specification Sheet

Operating Conditions

Type of fluid to be Filtered

Xylenes

Operating Pressure/Temperature

2.37Mpa(g) @ 175 °C

Flow

710.7m3/h

3kg/m3@PT

Density

867.4kg/m3@15°C, 727

10 um

viscosity

0.22cP@PT

Rating

Required Clean DP

by vendor

Required Dirty DP

0.15Mpa

Model

Housing

R48FC-4G193CH25P4-CC9406

Housing Part Number

g Required

4

Number of Housing

Pall China

Manufacture

GB150-98

Manufacture Code

g Housing material of Construction

304/316

Q345R

HOUS

g gure Seal

304/Graphite

Clos

Design Pressure/ Temperature

3.49Mpa @ 195°C

Dimensions

Φ600×H3438 (mm)

Volume capacity

0.70m³

Net Weight

1250kg

Inlet/Outlet

12" ASME 300# WNRF

Design Clean DP

0.20Mpa

0.92m³/a

Design Dirty DP

0.20Mpa

Design Flow

800m3/h

Element (for start-up)

Cartridge P/N

G100AW40S-1PK

Material

Heat Purified Glass Fiber

Manufacture

Pall USA

Required

192 pcs (48pcs per filter)

Number of Elements

0.205m²/pcs

Filtration Area

9.04m²

Total Area per filter

OD 2.1/2" x H 40"

Cartridge Description

Removal rating

100um (99%)

老



Pall Filter (Beijing) Co., Ltd

Dragon Aromatics (Zhangzhou) Co., Ltd

072000 电话: 4150511000-EN30-TER-0002

110004-1000-5100-5500-6000 电话: 021-62371968 Fax: 021-62371968

202A/B Desorbent Filters 21 E 41 E 202A/B 42 E

Specification Sheet

Operating Conditions

Type of fluid to be Filtered	PDEB+ C1
Operating Pressure/Temperature	2.37Mpa(195°C)
Flow	972.5m ³ /h
Density	865.6kg/m ³ @15°C, 743.3kg/m ³ @PT
Viscosity	0.25cp@DT
Rating	10 um
Required Dirty DP	0.15Mpa

Housing

Housing Part Number	872FC-462750-8-KDC00407
Number of Housing Required	4
Manufacture Code	GB150-90
Housing Material of Construction	Q345R
Closure Seal	304/Graphite
Design Pressure/ Temperature	3.73Mpa @ 195°C
Dimensions	Φ700×H3477 (mm)
Volume capacity	1.1m ³
Net Weight	1650 kg
Inlet/Outlet	14" ASME 300# WNRF
Designed Clean DP	0.02MPa
Designed Dirty DP	0.28MPa
Designed Flow	1100m ³ /h

for start-up) Element (for

Cartridge P/N

C100W40S-1PK

Heat Purified Glass Fiber Ball Filter

Heat Purified Glass Fiber Material

0.205m²/pcs
11.9m²

Filtration Area
Total Area per filter

Removal Rating

100um (99%)

2



P, Ltd
R-0002

Pall Filter (Beijing) Co., Ltd
Tel: 021-62371988 Fax: 021-62372088

Dragon Automatic (Zhangzhou) Co., Ltd
询价号: 413061-1000-EN30-TE

2.1.6 41-F-203A/B; 43-F-203A/B Backwash Filters

Specification Sheet

Operating Conditions

Flow	72.8m ³ /h
Density	746.1kg/m ³
Viscosity	0.21cp@PT
Rating	10 um
Required Dirty DP	0.15MPa

Housing

Housing Part Number	R07EC-4G65H25-CC9408
Number of Housing Required	4

Pall China
GB150-98

Manufacture Code

304/Granhite

Housing Material of Construction

Φ325×H2070(mm)

Dimensions

0.11m³

Volume capacity

4" ASME 300# WNRF

Inlet/Outlet

0.02MPa

Designed Clean DP

Designed Dirty DP

0.26mpa

Design Flow rate

80m³/h

Element (for start-up)

Cartridge P/N

G100AW40S-1PK

Material

Heat Purified Glass Fiber

Manufacture

Pall USA

Number of Elements Required

28pcs (7pcs per filter)

Filtration Area

0.205m²/pcs

Total Area per filter

1.435m²

Removal Rating

100um(99%)

2